



LUBE-A-SEAL™

ISO 9001: Certified

The Forefront of Lubrication Technology

Lube-A-Seal™ lubricant features lithium complex thickening agents designed to excel under conditions of extreme pressure and high temperatures, and it is equally suited for general-purpose use. Enhanced with state-of-the-art polymers, this lubricant boasts superior adhesiveness and film strength. It is meticulously crafted with specially selected mineral oils and fortified with additives, including extreme pressure, anti-wear, rust, and corrosion inhibitors, ensuring optimal lubrication for modern equipment.

Applications

Lube-A-Seal™ is an excellent choice when it comes to assisting in installation and extending the life of synthetic rubber products like O-rings, gaskets and seals.

This heavy-duty lubricant is tailored for demanding industrial environments characterized by intense heat, heavy loads, shear forces and water exposure. It excels in applications where shock loading is common, offering exceptional resistance against "squeeze out."

It finds its niche in mining and construction machinery, serving critical components like hitch pins, shackle pins, bushings and kingpins found on equipment such as buckets, excavators, shovels and loaders. Additionally, it's the go-to choice for slack adjusters in over-the-road trucks.

Wherever high temperatures and top-notch performance are prerequisites, Lube-A-Seal™ stands out as the ideal solution.

Advantages

- Versatile; High-temperature capable*; Performance-oriented
- Outstanding water resistance
- Exceptionally stable under shear stress
- Effective under extreme pressure; Offers anti-wear properties; Guards against corrosion
- Polymer enhanced for superior film strength in applications subject to shock loads
- Presented in a clean, off-white hue
- Adhesive for reliable adherence; Resistant to "squeezing out"



Available Options

- 5 gallon, 35 pound plastic pails
- 14 ounce tubes
- Mini packets: 1 gram, 2 gram or in ounces of customer's choice



Private labeling available.

**Lube-A-Seal™ operating temperature is 5°F – 248°F with a short-term peak of 350°F.*

Contact North Coast Seal today for more information!

Phone: **216-898-5000** Toll-Free: **1-800-770-7325** E-mail: **info@northcoastseal.com**

www.northcoastseal.com/lube-a-seal